

Tracking Efficiency in Z→ee

- Axial only CFT tracks
 - a lot of people worked hard to fit them into the d0reco
- Efficiency:
- p13.01
 - 3D: gtr+htf
 - 2D: gtr (chunk 113)
- patched p13
 - 3D: gtr + patched htf
 - 2D: gtr (chunk 113)
- plans

Axial Only tracks

- Present only in data path
- \bullet $Z_{DCA} = tg \lambda = 0$
- Vertex code filters them by requiring at least on SMT hit on a track
- ChargedParticle assigns $tg \lambda = 1000$ (and some non-zero errors on it and Z_{DCA})
- Physics objects are not affected since they match tracks to other subdetectors in eta-phi






Sample and Track matching

- CC-CC Z events from April to August, picked with calorimeter information
- pT correction: if no SMT hits, correct pT using DCA (as in p10.15 for ICHEP data)
- Match:
 - $\Delta(\phi_{\text{FM}}, \phi_{\text{track}}) < 50 \text{ mrad}$
 - pT > 5, 15 GeV
- "Fake" match:
 - $\Delta(\phi_{EM} + \pi/2, \phi_{track}) < 50 \text{ mrad}$
 - pT > 5, 15 GeV


Efficiency


$$\varepsilon_{track} = \frac{2 \cdot N_2 + N_1}{2 \cdot (N_2 + N_1 + N_0)}$$


p13



p13









live makines

p13 + patched htf



p13+patched HTF: FAKES



Efficiency

	3D tracks, pT>15GeV	3D tracks, pT> 5GeV	2D tracks, pT>15GeV	2D tracks, pT> 5GeV
p13	59.7±3.0	62.9±3.0	86.2±2.3	92.6±1.9
p13 patched HTF	71.1±2.8	74.8±2.7	87.4±2.1	93.0±1.8
p13 patched HTF FAKES	0.4 ± 0.2	1.1 ± 0.5	0.4 ± 0.2	1.7 ± 0.7

Summary

- Axial tracks proved to be quite usefull for analyses with high pT electrons and photons:
 - $P(e \rightarrow \gamma) = 0.069 \pm 0.018$
 - $P(\gamma \rightarrow e) = 0.017 \pm 0.007$
- May be useful for analysis of stereo inefficiencies
- There seems to be a drop in efficiency from p11 TARC to p13...

This document was created with Win2PDF available at http://www.daneprairie.com. The unregistered version of Win2PDF is for evaluation or non-commercial use only.